


DIN 582 Ring Nut, C15E steel, zinc plated and blue passivated



Type	Order Code	Inner Ø	Outer Ø	Weight	Box Quantity	Permissible Tension Load
		[mm]	[mm]	[kg/100 pcs]	[pcs]	F_1 [kN]
RM8-C15E	RMC0008	20	36	5	50	1.4
RM10-C15E	RMC0010	25	45	9	25	2.3
RM12-C15E	RMC0012	30	54	16	10	3.4
RM16-C15E	RMC0016	35	63	24	10	7.0
RM20-C15E	RMC0020	40	72	36	5	12.0

High Strength Ring Nut, 42CrMo4 steel, zinc plated and blue passivated



Type	Order Code	Inner Ø	Outer Ø	Weight	Box Quantity	Permissible Tension Load
		[mm]	[mm]	[kg/100 pcs]	[pcs]	F_1 [kN]
RMH8-HF	RMH0008	20	36	5	10	7.6
RMH10-HF	RMH0010	25	40	9	10	9.4
RMH12-HF	RMH0012	30	54	16	10	15.0
RMH16-HF	RMH0016	35	64	24	10	38.0

Hexagonal Screw Socket, steel, zinc plated and blue passivated



Type	Order Code	Internal Thread	Length	Width Across Flats	Weight	Box Quantity
		[mm]	L*	sw		
			[mm]	[mm]	[mm]	[kg/100 pcs]
GM6/20	GM0620	M6	20	9	2.5	200
GM8/25	GM0825	M8	25	11	3.3	200
GM10/30	GM1030	M10	30	13	6.0	100
GM12/35	GM1235	M12	36	17	12.0	50
GM16/40	GM1640	M16	40	22	16.0	25
GM20/50	GM2050	M20	50	24	20.0	25

*Maximum screw installation depth = L/2

Specials/Custom Anchors



Safety Bolt with Hexagonal Screw Socket



Safety Bolt with Extended Stud



Safety Bolt with Ring Nut

Specials also available with other products.